



GRIP




COLD



FIT

COLD-GRIP 47-180



CHARACTERISTICS

- Latex crinkle coating on the palm and fingers
- Acrylic terry liner (7 gauge)
- Elastic knitted wrist cuff
- Fully coated thumb for extra safety
- Soft and comfortable lining
- The ribbed profile of the latex coating provides excellent grip in dry and wet conditions
- The gloves retain the wearer's body heat, which makes them ideal for use in low temperatures
- Their dark colour makes these gloves excellently suitable for use in environments with a certain level of contamination

Article number: 1.47.180.00

SUITABLE FOR ACTIVITIES IN E.G.

- Construction
- Industry
- Transport & logistics
- Road work
- Maintenance
- Offshore

COLOUR

Black/grey

SIZES

8/M to 11/XXL incl.

PACKAGING

- 1 pair per headercard
- 12 pairs per bundle
- 72 pairs per outer box

EN388:2016
+A1:2018



2241X

EN511:2006



X2X

EN407:2020



X1XXXX



EN ISO 21420:2020

PRODUCT INFORMATION

SIZE	ARTICLE NO.	EAN CODE 1 PAIR (HEADERCARD)	EAN CODE 12 PAIRS (BUNDLE)	EAN CODE 72 PAIRS (OUTER BOX)
8/M	1.47.180.08	8718249009235	8718249009242	8718249036859
9/L	1.47.180.09	8718249009266	8718249009273	8718249036866
10/XL	1.47.180.10	8718249009297	8718249009303	8718249036873
11/XXL	1.47.180.11	8718249038709	8718249038716	8718249038723

COLOUR BINDING/OVERLOCKING

Sizes	8/M	9/L	10/XL	11/XXL
Colour binding/overlocking	green	blue	grey	black

CLARIFICATION OF PICTOGRAMS

EN388:2016
+A1:2018



2241X

EN388:2016
+A1:2018



ABCDEF

Protection against mechanical hazards

A = Scuff resistance (0-4)
B = Cut resistance (0-5)
C = Tear resistance (0-4)
D = Puncture resistance (0-4)
E = Cut resistance (in accordance with EN ISO 13997 (A to F))
F = Impact resistance (optional) (P = Passed)

EN407:2020



X1XXXX

EN407:2020



ABCDEF

Protection against heat and fire hazards

A = Limited flame spread (0-4)
B = Contact heat (0-4)
C = Convection heat (0-4)
D = Radiant heat (0-4)
E = Small drops of molten metal (0-4)
F = Large drops of molten metal (0-4)

EN511:2006



X2X

EN511:2006



ABC

Cold protection

A = Radiant cold (0-4)
B = Contact coldness (0-4)
C = Waterproofness (0-1)

Note: X = Not tested or not applicable

STORAGE CONDITIONS

The gloves should be kept in a clean, cool and dry place and not kept compressed in their original packaging. Do not expose the gloves to direct sunlight. Make sure that the packaging and the gloves are not damaged during shipping.

TESTING INSTITUTE

These gloves are certified by: CTC (Notified Body no. 0075), 4 Rue Hermann Frenkel 69367 Lyon, Cedex 07, France.

DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, we refer you to the following link: www.oxxa.work/doc

RELATED PRODUCTS



COLD-GRIP 47-185

Art. no. 1.47.185.00



X-GRIP-THERMO 51-850

Art. no. 1.51.850.00

YOUR SUPPLIER: