



LIQUID
PROOF



CHEMICAL
RESISTANT



GRIP

X-PRO-CHEM 51-900



Sanitized



CHARACTERISTICS

- Glove with full nitrile coating and nylon liner (18 gauge)
- Fitted with a double nitrile coating on the nylon liner with an additional third nitrile foam coating on the palm and fingertips
- The triple nitrile coating is exceptionally flexible and ensures a very good fit
- The rough 'Sandy finish' on the palm of the hand provides an excellent grip on dry, wet, greasy and oily objects
- Very comfortable to wear thanks to the soft nylon liner
- Extremely supple glove that protects the hand and forearm from a wide range of chemicals
- Sanitized treated to inhibit bacteria, minimise odours and improve freshness
- Free of harmful substances in accordance with OEKO-TEX® Standard 100
- Glove with scalloped edge (slip-on)
- Length: 350 mm
- Palm thickness: 1.2-1.4 mm / Back and cap thickness: 1.1-1.3 mm

Article number: 1.51.900.00

SUITABLE FOR ACTIVITIES IN E.G.

- Petrochemistry
- Industry
- Transport & logistics
- Cleaning services
- Shipping
- Agriculture
- Metal industry
- Offshore

COLOUR

Black/green

SIZES

8/M to 11/XXL incl.

PACKAGING

- 6 pairs per bundle
- 72 pairs per outer box

EN 388:2016
+A1:2018



4121X

EN ISO 374-1:2016
+A1:2018/Type A



AJKL MNPT

EN ISO 374-5:2016



VIRUS

EN 407:2020



X1XXXX

CE 0075
EN ISO 21420:2020

PRODUCT INFORMATION

SIZE	ARTICLE NO.	EAN CODE 12 PAIRS (BUNDLE)	EAN CODE 72 PAIRS (OUTER BOX)
8/M	1.51.900.08	8718249069543	8718249069581
9/L	1.51.900.09	8718249069550	8718249069598
10/XL	1.51.900.10	8718249069567	8718249069604
11/XXL	1.51.900.11	8718249069574	8718249069611

CLARIFICATION OF PICTOGRAMS

EN388:2016+A1:2018



4121X

EN388:2016+A1:2018



abcdef

Protection against mechanical hazards

A = Scuff resistance (0-4)
B = Cut resistance (0-5)
C = Tear resistance (0-4)
D = Puncture resistance (0-4)
E = Cut resistance (in accordance with EN ISO 13977 (A to F))
F = Impact resistance (optional) (P = Passed)
Note: X = untested or not applicable

EN407:2020



X1XXXX

EN407:2020



abcdef

Heat resistance

A = Flammability (0-4)
B = Contact heat (0-4)
C = Convection heat (0-4)
D = Radiation heat (0-4)
E = Small droplets of molten metal (0-4)
F = Large quantities of molten metal (0-4)

Note: X = not tested or not applicable

Protection against chemicals and microorganisms

EN ISO 374-1:2016+A1:2018/Type A		
Chemicals	EN 15523:2015 permeation level	
Methanol (A)	2	
n-Heptane (J)	6	
40% Sodium Hydroxide (K)	6	
96% Sulphuric Acid (L)	3	
65% Nitric acid (M)	3	
99% Acetic acid (N)	2	
25% Ammonium hydroxide (O)	3	
30% Hydrogen peroxide (P)	6	
37% Formaldehyde (T)	6	

EN 374-4:2019	
Cos nummer	Klasse
(A) 67-56-1	Primary alcohol
(J) 142-82-5	Saturated hydrocarbon
(K) 1310-73-2	Inorganic base
(L) 7664-93-9	Inorganic mineral acid, oxidizing
(M) 7697-37-2	Inorganic mineral acid, oxidizing
(N) 64-19-7	Organic acid
(O) 1336-21-6	Organic base
(P) 7722-84-1	Peroxide
(S) 7664-39-3	Inorganic mineral acid
(T) 50-00-0	Aldehyde

Resistant against bacteria, mould and viruses

Chemicalie	Mean Degradation %
Methanol (A)	33.7%
n-Heptane (J)	-9.2%
40% Sodium Hydroxide (K)	-12.5%
96% Sulphuric Acid (L)	65.3%
65% Nitric acid (M)	53.1%
99% Acetic acid (N)	56.7%
25% Ammonium hydroxide (O)	29.5%
30% Hydrogen peroxide (P)	18.5%
37% Formaldehyde (T)	28.6%

EN ISO 374-5:2016		
EN ISO 374-5:2016	Resistance against bacteria and mould	Resistance against viruses
VIRUS	PASS	PASS

EN 374-2:2019	
Air leak test - Pass	Water leak test - Pass

EN ISO 374-1:2016 Permeation levels are based on the following breakthrough times:

Performance level	1	2	3	4	5	6
Minimal breakthrough times (in min.)	>10	>30	>60	>120	>240	>480

STORAGE CONDITIONS

The gloves should be kept in a clean, cool and dry place and not kept compressed in their original packaging. Do not expose the gloves to direct sunlight. Make sure that the packaging and the gloves are not damaged during shipping.

TESTING INSTITUTE

These gloves are certified by: CTC (Notified Body nr 0075), 4 Rue Hermann Frenkel 69367 Lyon, Cedex 07, France.

DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, we refer you to the following link: www.oxxa-safety.com/doc

GERELATEERDE ARTIKELN



NITRILE-CHEM 41-200
Art. nr. 1.41.200.00



EGON 8226
Art. nr. 7.78.226.00

