



GRIP




CUT
RESISTANCE



COMFORT

E-MISSION- PRIME CUT D 52-720



CHARACTERISTICS

- PFT (Premium Foam Technology) nitrile coating on palm and fingers
- 32% Recycled polyester/Tencel/HPPE/Steel wire/nylon/Spandex backing (18 gauge)
- Seamless glove with an elastic knit wrist cuff
- Sustainably produced soft Tencel fibers combine with the other fibers to provide very good cut resistance and excellent comfort
- PFT coating provides excellent grip in dry, wet, greasy and oily conditions
- Equipped with an additional nitrile reinforcement between the thumb and index finger (crotch)
- Very good ventilation on back of hand keeping hands dry and cool
- Super light coating offers a high degree of dexterity and flexibility
- Conductive coating on the fingers ensures perfect operation of all touchscreen devices
- Sanitized® treated to inhibit bacteria, minimize odors and promote freshness

Article number: 1.52.720.00

SUITABLE FOR ACTIVITIES IN E.G.

- Glass industry
- Metalworking
- Transport & logistics
- Construction
- Automobile

COLOR

Black/pepper & salt

SIZES

7/S to 11/XXL

PACKAGING

- 1 pair per headercard
- 6 pairs per bundle
- 72 pairs per outer box

Sanitized®

EN388:2016
+A1:2018



4X42D

EN407:2020



X1XXXX



TOUCHSCREEN
CAPABILITY



EN ISO 21420:2020

PRODUCT INFORMATION

SIZE	ARTICLE NO.	EAN CODE 1 PAIR (HEADERCARD)	EAN CODE 6 PAIRS (BUNDLE)	EAN CODE 72 PAIRS (OUTER BOX)
7/S	1.52.720.07	8718249072048	8718249072093	8718249072147
8/M	1.52.720.08	8718249072055	8718249072109	8718249072154
9/L	1.52.720.09	8718249072062	8718249072116	8718249072161
10/XL	1.52.720.10	8718249072079	8718249072123	8718249072178
11/XXL	1.52.720.11	8718249072086	8718249072130	8718249072185

PIPING COLOR

Sizes	7/S	8/M	9/L	10/XL	11/XXL
Piping color	yellow	green	blue	gray	black

CLARIFICATION OF PICTOGRAMS

EN388:2016
+A1:2018



4X42D

EN388:2016
+A1:2018



ABCDEF

Protection against mechanical hazards

- A = Scuff resistance (0-4)
- B = Cut resistance (0-5)
- C = Tear resistance (0-4)
- D = Puncture resistance (0-4)
- E = Cut resistance (in accordance with EN ISO 13997 (A to F))
- F = Impact resistance (optional) (P = Passed)

EN407:2020



X1XXXX

EN407:2020



ABCDEF

Protection against heat and fire hazards

- A = Limited flame spread (0-4)
- B = Contact heat (0-4)
- C = Convection heat (0-4)
- D = Radiant heat (0-4)
- E = Small drops of molten metal (0-4)
- F = Large drops of molten metal (0-4)

Note: X = untested or not applicable

STORAGE CONDITIONS

The gloves should be kept in a clean, cool and dry place and not kept compressed in their original packaging. Do not expose the gloves to direct sunlight. Make sure that the packaging and the gloves are not damaged during shipping.

TESTING INSTITUTE

These gloves are certified by: CTC (Notified Body no: 0075), 4 Rue Hermann Frenkel 69367 Lyon, Cedex 07, France.

DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, we refer you to the following link: www.oxxa.work/doc



RELATED ECO PRODUCTS



E-MISSION
CUT C 52-700

Art. no. 1.52.700.00

YOUR SUPPLIER: