



User instructions Heatbeater 2

General maintenance instructions:

- Follow the washing prescription and other instructions at all times.
- Clean and inspect gloves before and after use to detect any possible damage. Avoid wearing the gloves if dirty on the inside, to avoid any skin reactions.
- Very filthy or damaged gloves can affect the function and the level of protection. Replace the gloves regularly and replace them when necessary. If defect then dispose the gloves in the residual waste.
- If the risks or circumstances in which the gloves are used change, contact a safety manager to be sure that the gloves are also suitable for the new circumstances.
- Do not repair the gloves yourself.
- The performance levels of the gloves are in correspondence to the current European norms.
- The gloves are tested to be used up to 350 degrees Celsius for a short period of time.
- The overall classification does not necessarily reflect the performance of only the outer layer of the glove or mitten.
- It is not recommended to expose the glove directly to an open flame.
- The gloves should not be worn when there is a risk of being caught up in moving parts of machinery.

Washing prescription for this model:



The surface of the glove can be cleaned using a cloth soaked in warm water or by using a soft-haired brush, then store it under normal and dark conditions. Store the product in dry conditions at a temperature between 0 and 30 degrees Celsius. UV radiation can affect the quality of the gloves.

Composition:

- Heavy-duty Para-Aramid felt- palm- back- cuff - outer layer
- Light-duty Para-Aramid felt - lining

For as far the manufacturer knows the materials do not contain substances which can cause allergic reactions.

Sizes of the gloves: Size 11.

The gloves are manufactured in size 11, but in several lengths. In all circumstances the gloves can be thrown out in case of an

Available length + article number:


- Length 32 cm: 022521320
- Length 42 cm: 022521420
- Length 60 cm: 022521600
- Length 80 cm: 022521800





User instructions Heatbeater 2

EN 388:2016



2 Abrasion
5 Blade cut
4 Tear
4 Puncture
E Cut

A. Abrasion Min. 0; Max. 4
B. Cut resistance Min. 0; Max. 5
C. Tear resistance Min. 0; Max. 4
D. Puncture resistance Min. 0; Max. 4
E. Cut resistance (TDM, EN ISO 13997) Min. A; Max. F
F. Shock protection P= Successful

EN 407: 2004



4 Burning Behaviour
3 Contact heat
x Convective Heat
x Radiant Heat
x Small drops molten metal
x Large drops molten metal

A. Burning behaviour Min. 0; Max. 4
B. Contact heat Min. 0; Max. 4
C. Convective heat Min. 0; Max. 4
D. Radiant heat Min. 0; Max. 4
E. Small drops of molten metal Min. 0; Max. 4
F. Large drops of molten metal Min. 0; Max. 4



This product is certified according to Regulation (EU) 2016/425 and is a category III article. This product is designed to determine the protection specified in EN 388: 2016 (protection against mechanical risks), EN 420: 2003 + A1: 2009 (general requirements) and EN 407: 2004 (thermal risks) with the detailed level of the performance presented below. However, always bear in mind that no PPE item can offer complete protection and that caution should always be exercised when exposed to risks. Category III PPE: Annual follow-up according to Module C2 & EU type certificate (module B) issued by Centexbel (NB 0493), Technologiepark 70, 9052 Zwijnaarde (Belgium).

The EU Declaration of Conformity is available at:

<https://www.ppe-factory.com/wp-content/uploads/2021/06/D.O.C.-Heatbeater-1-2.pdf>