

Vital 180

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Natural latex blended nitrile
- **Length (inches)** 12.20
- **Thickness (inches)** 0.0157
- **Wrist** Straight cuff
- **Colour/Color** Red
- **Interior finish** Flocked
- **Exterior finish** Embossed texture, chlorinated
- **Size / EAN** 6 7 8 9 10
- **Packaging** 1 pair/bag - 10 pairs/box - 100 pairs/carton
- **Complementary information** Guaranteed without silicone



PERFORMANCE RESULTS

Certification category 3

CE 0334



Dexterity EN 420 : 5/5



1110X

Legends

EN 388 MECHANICAL HAZARDS



PERFORMANCE LEVELS

0-4 0-5 0-4 0-4 A-F (P)
 Impact protection
 Cut resistance according to ISO 13997
 Puncture resistance
 Tear resistance
 Blade cut resistance
 Abrasion resistance

EN 407 THERMAL RISKS heat and fire



PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4
 Resistance to large quantities of molten metal
 Resistance to small drops of molten metal
 Radiant heat resistant
 Convective heat resistance
 Contact heat resistance
 Burning behaviour

CHEMICAL RISKS

EN ISO 374-1



Type A

U V W X Y Z

A Methanol
 B Acetone
 C Acetonitrile
 D Dichloromethane
 E Carbon Disulfide
 F Toluene
 G Diethylamine
 H Tetrahydrofuran
 I Ethyl acetate

EN ISO 374-1



Type B

X Y Z

J n-Heptane
 K Sodium hydroxide 40%
 L Sulphuric acid 96%
 M Nitric acid 65%
 N Acetic acid 99%
 O Ammonia 25%
 P Hydrogen peroxide 30%
 S Hydrofluoric acid 40%
 T Formaldehyde 37%

EN ISO 374-1



Type C

MICRO-ORGANISMS

EN ISO 374-5



Potential against bacteria, fungi

EN ISO 374-5



Potential against bacteria, fungi, virus

VIRUS



COLD HAZARDS

PERFORMANCE LEVELS

0-4 0-4 0 or 1
 Water permeability
 Contact cold resistance
 Convective cold resistance



RADIOACTIVE CONTAMINATION



CUT

CUT RESISTANCE

A1 ≥ 200 G A4 ≥ 1500 G A7 ≥ 4000 G
 A2 ≥ 500 G A5 ≥ 2200 G A8 ≥ 5000 G
 A3 ≥ 1000 G A6 ≥ 3000 G A9 ≥ 6000 G

For more details: www.mapa-pro.com

MAPA
PROFESSIONAL

www.mapa-pro.com

SPECIFIC ADVANTAGES

- Comfortable cotton flock-lining
- Chlorinated finish for better protection of products being handled
- Previous name : Duo-Nit 180

MAIN FIELDS OF USE

Other industries

- Cleaning and general maintenance in wet environments

Mechanical industry

- Assembly of small oily parts

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the "CE"-type tests.
- It is not recommended for persons sensitised to natural latex, thiurames, dithiocarbamates and thiazoles to use these gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the Technical Customer Service - MAPA PROFESSIONNEL (stc.mapaspontex@mapaspontex.fr) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Inspect the gloves for cracks or snags before reusing them.

Storage conditions

- Store the gloves in their original packaging protected from direct sunlight, far from heat sources or electric equipment.

Laundering conditions

- Before taking off the gloves, clean them as appropriate :
- in use with a solvent (alcohol, etc...) : rub over with a dry cloth,
- in use with acids or alkalies : thoroughly rinse the gloves under running water and rub over with a dry cloth.
- Caution : using the gloves or submitting them to another cleaning or laundering process can alter their performance levels .

Drying conditions

- Ensure the inside of the gloves is dry before putting them on again.

LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- **UE type certificate or CE type examination certificate** : 0075/014/162/08/18/1638
- **Issued by the notified body nr** : 0075 - CTC - 4,rue Hermann Frenkel - 69367 Lyon cedex 07-France
- **Quality assurance certificat** : 0334 Asqual 14 rue des Reculettes -F-75013 PARIS