

Product Datasheet model ultravision 9301 105



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

Product characteristics	* Anatomical shape and soft material allow close, yet comfortable fit * Fits comfortably over most prescription spectacles * Nose bridge works well with respirators * Frosted top to reduce glare * High-quality, easily adjustable headband * Optically correct lens (EN 166 class 1) does not distort view or cause headaches * Simple lens replacement reduces cost * Chemical resistant outside, antifog inside of lens
Technical details Frame Material Features Colour	Front piece PVC ventilation system transparent light grey

Material	Headband
Features	synthetic headband
Colour	adjustable
	anthracite/lime
Manufacturer's ID	Marking
code	W
Applicable EN norm	166
Field of use	3 (drops and splashes of liquid)
	4 (large dust particles)
	9 (molten material and hot solids)
Medium-energy impact	B (120 m/s)
Tested acc. to DIN	DIN
No. of certificat. body	0196
Conformity symbol	CE
Lens	
Material	PC
Filter	2,2 mm
Coating	supravision excellence
Colour	clear
Filter	Marking
Manufacturer's ID	2C-1,2 (DIN EN 170)
code	W
Optical class	1
Low-energy impact	B (120 m/s)
Field of use	9 (molten material and hot solids)
Surface resistance to fine particles	K
Antifog	N
Tested acc. to DIN	DIN
Conformity symbol	CE

Miscellaneous	
Weight	130 g
Packing	90 pieces in one carton
Standards	DIN EN 166 + DIN EN 170