



LED LIGHT VISION

Clear Hardium+ lens with 2 LED's



FRAME

- Wraparound polycarbonate frame with rubber
- Soft, rubber shroud for superior comfort and protection
- Integrated side and orbital protection
- 2 adjustable ultra-bright LED's with long battery life (over 50 hours - model Lithium CR2032)
- The 4 batteries are included (2 per LED)
- Rubber temples and nose pads for extra-comfort
- Heat resistance : up to 90° C
- Weight : 50 g.

LENS

- Clear Polycarbonate wraparound lens for excellent field of vision and lateral coverage
- Optical quality class 1 (no distortion)
- Resistance to impact at extreme temperature
- 100% UV filtration (in conformity with EN170)
- Hardium+ technology = superior anti-scratch and anti-fog coating
- Visible Light Transmittance = 92%

FIELDS OF USE

- Mechanical hazards (marking F - 45m/s)
 - solid particles projectiles (metal, wood...) riveting, grinding, stone cutting, drilling...
- Electrical work, car repair, plumbing,
- home-work, mechanical work...
- UV radiation (accidental electric arc)
- Mist

DO NOT USE FOR

Does not protect against liquid, dust, molten metal, laser beam, or any kind of welding application.

FRAME MARKING

CE AOS 166 FT

CE = conformity marking
 AOS = manufacturer Aearo
 166 = n° of the standard
 FT = impact resistance at extreme temperature (45m/s between -5° and +55°C)

EUROPEAN STANDARD

This product conforms to the European Council Directive 89/686/EEC and with the EN166 : 2001

EC-Type Examination Certificate n° 1570

Issued by INSPEC (notified body n°0194)
 Upper Wingbury Courtyard, Wingrave, Aylesbury
 Buckinghamshire, HP22LW, England

Conform to EN166 - EN170

LENS MARKING

2C-1,2 . AOS . 1 . FT

2C = UV filter with good color recognition (conform to EN170)
 1,2 = shade number (clear lens)
 AOS = manufacturer Aearo
 1 = optical class (permanent wear)
 FT = impact resistance at extreme temperature (45m/s between -5° and +55°C)

PRODUCT REFERENCE

Product Code	Frame	Lens	Material
11356-00000P			PC Hardium+

Supplied with a microfiber pouch

