uvex	**SAFETY EYEWEAR**	21.09.2015 SBU-E-PGM-PM

Product Datasheet model i-3 9190 315

UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth

Product characteristics	* Innovative protective spectacle, perfectly fit the face * Individually adjustable side arms with variable inclination * Integrated Softflex zone ensures outstanding wearer comfort for all head sizes * Softflex nose piece ensures comfortable, pressure-free fit and remain firmly in place * Soft ear and Softflex bridge pieces ensure a secure fit in any situation
Technical details **Frame** Material Features Colour	 **Front piece/Temple** TPU/TPE variable inclination, individually adjustable white-lime

	Marking
Manufacturer's ID code	W
Applicable EN norm	166
Low-energy impact	F (45 m/s)
Resistance to high speed particles at extremes of temperat.	T
Conformity symbol	CE
No. of certificat. body	0196
Lens	
Material	PC
Thickness	2,2 mm
Coating	supravison excellence
Colour	clear
	Marking
Filter	2C-1,2 (DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Low-energy impact	F (45 m/s)
Resistance to high speed particles at extremes of temperat.	T
Surface resistance to fine particles	K
Antifog	N
Conformity symbol	CE

Miscellaneous	
Weight	30 g
Packing	5 spectacles per box 160 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 170