


DENALI 4050



CHARACTERISTICS

- Fall arrest device for the use of 11 mm diameter polyamide core kernmantle rope lifelines
- Fitted with a steel karabiner (opening 18 mm)
- Has a manually locked position for work on sloping roofs as well as a blocking mechanism
- Ultra-simple opening/closing system
- Maximum resistance: 15 kN

Article number: 8.84.050.00

SUITABLE FOR WORK IN, E.G.:

- Scaffolding
- Construction
- Installation technology
- Aerial platforms
- Offshore
- Petrochemicals

COLOUR

Black

PACKAGING

- 1 piece per polybag
- 20 pieces per case

CE 0598
EN 353-2:2002

ITEM INFORMATION

SIZE	ARTICLE NO.	EAN CODE 1 PIECE (POLYBAG)	EAN CODE 20 PIECES (CASE)
One size	8.84.050.00	8718249047268	8718249047275

STORAGE REQUIREMENTS

During transportation, keep the equipment away from any sharp edges and in its packaging. Clean with water, wipe with a cloth and hang in a ventilated room to dry naturally, ensuring that it is away from any direct light or source of heat; the same applies for elements that may have got wet during use. The system must be stored in its packaging in a dry, well-aired place protected from temperature extremes.

TESTING INSTITUTE

This fall protection is certified by: SATRA Technology Europe Ltd (Notified Body no. 2777), Bracetown Business Park, Clonree, Dublin D15 YN2P, Ireland.

DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, please refer to the following web link:
www.oxxa-safety.com/doc


RELATED PRODUCTS



FUJI 4015

Harness 3D

Article no. 8.84.015.00



OERAL 4102

Kernmantle rope fall protection lanyard, 11 mm 20 m

Article no. 8.84.102.00



MOCO 4180

Sling anchor point 120 cm

Article no. 8.84.180.00

YOUR SUPPLIER: