


TAUNUS 4170



CHARACTERISTICS

- Automatically retracting fall arrest device with 50 mm strap and fall absorber
- Includes a snap hook (opening 16 mm) and a steel scaffold hook (opening 50.8 mm)
- Protective housing
- Equipped with an NFC chip under the label that is intended for mapping users and keeping track of inspection intervals
- Suitable for vertical use (maximum 100 kg)
- The maximum angle of inclination is 40°
- Length: 2.5 meters
- Maximum load: 15 kN
- Fall factor 0

Article number: 8.84.170.00

SUITABLE FOR ACTIVITIES IN E.G.

- Scaffolding construction
- Construction
- Installation technology
- Aerial work platforms
- Offshore
- Petrochemistry

PACKAGING

- 1 piece per polybag
- 10 pieces per outer box

CE 0598
EN 360:2002

PRODUCT INFORMATION

SIZE	ARTICLE NO.	EAN CODE 1 PIECE (POLYBAG)	EAN CODE 10 PIECES (OUTER BOX)
One size	8.84.170.00	8718249047688	8718249047695

STORAGE REQUIREMENTS

During transportation, keep the unit away from any sharp parts and store it in its packaging. Clean with soap and water. Wipe with a cloth and hang in a ventilated area so that it can dry naturally and away from any open fire or heat source. This also applies to parts that have become wet during use. The device should be stored in its packaging in a dry and ventilated area with moderate temperatures.

TESTING INSTITUTE

This fall protection has been certified by: SATRA Technology Europe Ltd (Notified Body no. 2777), Bracetown Business Park, Clonree, Dublin D15 YN2P, Ireland.

DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, please refer to the following web link: www.oxxa.work/doc

RELATED ARTICLES



FUJI 4015

Harness 3D

Art. no. 8.84.015.00



ANDES 4013

Harness 5D

Art. no. 8.84.013.00

YOUR SUPPLIER: