

MOKE 4180

CHARACTERISTICS

- Mobile anchor point made of polyester webbing
- Length: 120 cm
- Width: 20 mm
- Maximum resistance > 18 kN

Article number: 8.84.180.00

SUITABLE FOR WORK IN, E.G.:

- Scaffolding
- Construction
- Installation technology
- Aerial platforms
- Offshore
- Petrochemicals

PACKAGING

- 1 piece (polybag)
- 50 pieces (case)

CE 0598

EN 795:2012 (Type B)



ITEM INFORMATION

SIZE	ARTICLE NO.	EAN CODE 1 PIECE (POLYBAG)	EAN CODE 10 PIECES (CASE)
One size	8.84.180.00	8718249047701	8718249047718

STORAGE REQUIREMENTS

During transport, keep the securing strap away from all cutting parts and keep it in its bag. Clean with water, dry with a cloth and hang in a ventilated area to dry naturally and away from any naked flame or heat source, same for the parts that have become damp during use. The belay strap should be stored in its bag in a dry and ventilated room with a moderate temperature. Make sure to keep it away from any heat source.

TESTING INSTITUTE

This fall protection is certified by: SATRA Technology Europe Ltd (Notified Body no. 2777), Bracetown Business Park, Clonee, Dublin D15 YN2P, Ireland.

DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, please refer to the following web link:
www.oxxa-safety.com/doc

YOUR SUPPLIER: