

Drain Couplings are designed for use in drainage systems, where the resistance to earth loads and shear forces provided by a shear band is not required. They are available to joint drainage pipes up to 225mm diameter.

Due to the use of modern fabrication methods any coupling can be supplied to site within 24 hours.

## Uses

- As a joint for plain ended pipe.
- The repair of an existing drain by the insertion of a new length of pipe.
- As an adaptor between pipes of different materials.
- Jointing short or cut lengths of pipe.
- Provision of rocker pipes adjacent to structures.

## DRAIN COUPLINGS • 50 - 225mm

REFERENCE NUMBER	SIZE RANGE (mm)	WIDTH (mm)	T (mm)
MDC 100	85 - 100	100	7
MDC 115	100 - 115	120	7
MDC 122	107 - 122	120	7
MDC 135	120 - 135	120	7
MDC 150	135 - 150	120	7
MDC 165	150 - 165	120	7
MDC 175	160 - 175	120	7
MDC 195	180 - 195	120	7.5
MDC 212	197 - 212	120	7.5
MDC 225	210 - 225	120	7.5

Also produced in Nitrile rubber and with grade 1.4401 (316) stainless steel fittings. Please contact us for availability.



## DRAIN COUPLINGS APPLICATION SCHEDULE

**MDC115** 110mm PVCu  
100mm Cast Iron (Soil) (SMU/Ensign/SML)  
100mm Stainless Steel  
100mm Corrugated Plastic  
110mm Corrugated Plastic

**MDC125** 100mm Supersleve  
100mm Cast Iron (Drain)  
100mm Ductile Iron  
100mm Grey Iron  
100mm Asbestos Cement  
100mm Pitch Fibre  
100mm Twin Walled Plastic

**MDC135** 100mm Supersleve  
100mm (4") Salt Glazed Ware  
100mm Vitrified Clay  
100mm Pitch Fibre  
100mm Asbestos Cement

**MDC150** 125mm Cast Iron (Soil)  
125mm Twin Walled Plastic

**MDC165** 160mm PVCu  
150mm Cast Iron (SMU/Ensign/SML)  
150mm Stainless Steel  
160mm Polyethylene

**MDC175** 150mm Ultra-Rib  
150mm Quantum  
150mm Ductile Iron  
150mm Grey Iron  
150mm Twin Walled Plastic (Wavin/Norflex)  
150mm Corrugated Plastic (Wavin/Aquapipe)

**MDC195** 150mm Supersleve  
150mm (6") Salt Glazed Ware  
150mm Vitrified Clay  
150mm Concrete  
150mm Asbestos Cement  
150mm Pitch Fibre