



Product name : **DHF-PVC anti-corrosive solenoid valve**

Item :

Details :

Characteristic: 1.With isolated diaphragm
 2.PVC body for corrosion resistant
 3.Suitable for applications with temperature below 60°C

Medium: Corrosive fluid and gas, Acid, Alkali, etc.

Pressure: DHF-U: 0 ~ 3 bar NC

Port Size: 1/2", 3/4", 1", 1 1/4", 1 1/2", 2"

Port Thread: BSPP,

Orifice (mm): 15, 20, 25, 32, 40, 50

Voltage: 220V/50HZ

Tolerance: +/- 10%

Coils: IP65, 100%ED

Material: Body - PVC
Seal - EPDM
Armature Tube - Stainless Steel 304
Plunger - Stainless Steel 430F
Stop -SS430F

PVC solenoid valve, Normally Closed, with Coil 22-240V AC

Model	Port Size	Orifice(mm)	Cv	Min Pressure(bar)	MAX Pressure(bar)	
					AC(6VA)	DC(5W)
DHF21-15	1/2"	15	3.5	0	3	3
DHF21-20	3/4"	20	7	0	3	3
DHF21-25	1"	25	11	0	3	3
DHF21-32	1 1/4"	32	14	0	3	3
DHF21-40	1 1/2"	40	24.5	0	3	3
DHF21-50	2"	50	35	0	3	3
