

#### SAFETY DATA SHEET

SafeBase 2.5 "B" Component Revised Date: 8/24/2016

> Version: 1 SDS-147

#### **SECTION 1: IDENTIFICATION**

PRODUCT NAME **CAS NUMBER PRODUCT USE DISTRIBUTOR ADDRESS** 

**PHONE** FAX

**EMERGENCY CONTACT** 

**TOLL FREE** INTERNATIONAL FAX

SafeBase 2.5 "B" Component

Not available Polyurethane Foam Safe Basements LLC

60335 US HWY 12, Litchfield, MN 55355

800-430-5851 Not available

FOR SPILLS, LEAKS, FIRE, OR EXPOSURE CALL CHEMTREC

800-424-9300 +1-703-527-3887 913-321-1490

#### **SECTION 2: HAZARDS IDENTIFICATION**

#### **GHS CLASSIFICATION**

**GHS PICTOGRAM** 



# **NEW GHS SCALE**





### **WARNING**

#### Personal Protective Equipment



GHS SCALE Extreme

Moderate









#### **EMERGENCY OVERVIEW**

HAZARD STATEMENTS			PRECAUTIONARY STATEMENTS		
H315	Causes skin irritation.	P264	Wash hands thoroughly after handling.		
H320	Causes eye irritation.		Wear protective gloves/protective clothing/eye protection/ face protection.		
H333	May be harmful if inhaled.	P261	Avoid breathing dust/fumes/gas/mist/vapors /spray.		
H335	May cause respiratory irritation.	P271	Use only out doors or in a well-ventilated area.		
H302	Harmful if swallowed.	P270	Do not eat, drink, or smoke when using this product.		
		P285	In case of inadequate ventilation wear respiratory protection.		

APPEARANCE, COLOR, ODOR:

Liquid, light yellow, amine odor.

USA: This material is not hazardous to health by the OSHA Hazard Communication Standard (29 CFR 1910-1200). READ THE ENTIRE SDS FOR MORE THOROUGH EVALUATION OF THE HAZARDS

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS		
CHEMICAL NAME	CAS NUMBER	% WEIGHT
Polyether polyol	25791-96-2	40-70
Polyether polyol	9049-71-2	20-40
Triethanolamine	102-71-6	1-10
Ethanol, 2-(dimethyamino)-	108-01-0	1-10
Dipropylene glycol	25265-71-8	<1
Triethylenediamine	280-57-9	<1
Copolymer of dimethylsiloxane and polyoxyalkyene	68937-45-2	<1
Dibutylin dilaurylmercaptide	1185-81-5	<1

SECTION 4: FIR	ST AID MEASURE	:S		
EYE: H320		Causes eye irritation. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do, continue rinsing. IF eye irritation persists: Get medical advice/attention.		
SKIN:	H315	Causes skin irritation. IF ON SKIN: wash with plenty of soap and water. IF SKIN irritation or rash occurs: Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell.		
INHALATION:	H333/335	May be harmful if inhaled and may cause respiratory irritation. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.		
INGESTION:	H302	Harmful if swallowed. IF SWALLOWED: Rinse mouth. Call a POISON CENTER or doctor, physician IF you feel unwell.		
NOTES TO PHYS	SICIAN:	Symptomatic and supportive therapy as needed. Following severe exposure, medical follow-up should be monitored for 48 hours.		
SECTION 5: FIRE	FIGHTING MEAS	SURES TO THE REPORT OF THE PROPERTY OF THE PRO		
FLASH POINT:		Not available.		
HAZARDS WHE NEAR FLAME:	N ON FIRE OR	May produce toxic fumes of carbon dioxide, carbon monoxide, ammonia, ketones, nitrogen oxides, and formaldehyde when near heat source/flame. This product contains Ethanol, 2-(dimethylamino), at 3.7%, may lead to the formation of explosive vapors. When in a closed container, pressure will increase which may lead to a rupture of the container.		
SUITABLE EXTINGUISHING MEDIA:		Water, dry extinguishing media, carbon dioxide, foam.		
UNSUITABLE EXTINGUISHING MEDIA:		None known.		
SPECIAL EXPOSURE HAZARDS:		Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. If in a fire or heated, a pressure increase will occur and the container may rupture.		
SPECIAL PROTE EQUIPMENT FO FIGHTERS:		Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. PVC boots, gloves, safety helmet, and protective clothing should be worn.		
SECTION 6: ACC	IDENTAL RELEA	SE MEASURES		
ACCIDENTAL REMEASURES:	ELEASE	For major spills call <b>CHEMTREC</b> : Toll free <b>1-800-424-9300</b> for international call <b>1-703-527-3887</b> .		
PERSONAL PRECAUTIONS:		Wear appropriate personal protective equipment recommended in SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION of this SDS. Immediately contact emergency personnel. Evacuate the area. Keep upwind avoiding inhalation of vapors Clean-up should only be performed by trained personnel. People dealing with major spillages should wear full protective clothing including respiratory protection.		
ENVIRONMENTAL PRECAUTIONS:		This material may contaminate the environment without proper control and response to spills. Ensure spilled material does not come in contact with soil, waterway, drains sewers, or other runoff that would further disperse the material. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, so air). Sources of ignition should be kept clear.		
METHODS FOR	CONTAINMENT:	Use diking or capping to control migration. Contain and absorb large spillages with a non-flammable absorbent carrier (such as vermiculite, earth, or sand). DO NOT USE combustible materials such as sawdust. Shovel into open-top drums or plastic bags for further decontamination, if necessary. Remove and properly dispose of residues. Dispose of via a licensed waste disposal contractor (See SECTION 13: DISPOSAL CONSIDERATIONS) Notify applicable government authorities if release is reportable.		

METHODS FOR CLEANING UP	LIP	ING	INA	IFΔ	CI	FOR	DS	OH	METH
-------------------------	-----	-----	-----	-----	----	-----	----	----	------

Only proceed with clean up by taking the appropriate personal protection measures required and ensure surrounding area does not contain further hazards that could worsen the spill, cause migration, or cause further harm (i.e. eliminate any ignition sources). Move any non-contaminated, non-leaking containers from the spill zone if it can be done safely. Dike, dam, or further restrict and stop active leaks without posing further damage or harm to individuals, the environment, and/or structures. Contain and collect spillage. See SECTION 13: DISPOSAL CONSIDERATIONS for disposal information and SECTION 8: EXPOSURE CONTROL/ PERSONAL PROTECTION for recommended Personal Protective Equipment (PPE). Obey all local, state, and federal regulations during clean up.

#### **SECTION 7: HANDLING & STORAGE**

GENERAL:	Ideal storage temperature is 60-90°F (15-32°C). Handling and storage shall be in accordance with local, state/provincial, or federal regulations.
HANDLING:	Before opening this package, read and follow warning labels on all components. Avoid contact with the product or reaction mixture. Put on appropriate personal protective equipment. Use only with adequate ventilation to ensure that the occupational exposure limit is not exceeded, use respirator when ventilation is inadequate. Avoid breathing aerosols, mists, and vapors. (See SECTION 8: EXPOSURE CONTROL/ PERSONAL PROTECTION for details). Do not ingest. Eating, drinking, and smoking shall be prohibited in areas where this material is handled, stored, and processed. Workers shall wash hands and face before eating, drinking, and smoking. Persons with a history of skin sensitization problems, asthma, allergies, or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Do not get in eyes, on skin, or clothing. Keep in the original container or an approved alternative made from a compatible material. Kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse containers.
STORAGE:	Keep container tightly closed and properly sealed when stored. When possible, store product indoors in a dry, well-ventilated area. Store in original container protected from direct sunlight, away from incompatible materials, and away from food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers and use appropriate containment to avoid environmental contamination.

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **EXPOSURE LIMITS:**

COMPONENT NAME	CAS NUMBER	EXPOSURE LIMITS		
Polyether polyol	25791-96-2	Not available		
Polyether polyol	9049-71-2	Not available		
Triethanolamine 102-71-6		ACGIH TWA: 5.0 0.1 mg/m³ TWA: 1.0 0.1 mg/m³ (Inhalable fraction and vapor)		
Ethanol, 2-(dimethyamino)-	108-01-0	Not available		
Dipropylene glycol 25265-71-8		Not available		
Triethylenediamine 280-57-9		Not available		
Copolymer of dimethylsiloxane 68937-45-2 and polyoxyalkyene		Not available		
Dibutylin dilaurylmercaptide	1185-81-5	ACGIH TWA: 0.1 mg/m³ STEL: 0.2 mg/m³ OSHA PEL: 0.1 mg/m³ TWA: 0.1 mg/m³ NIOSH REL: 0.1 mg/m³		

ENGINEERING CONTROLS:	mist, use process enclosures, lo	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor, or mist, use process enclosures, local exhaust ventilation, and other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.			
HYGIENE MEASURES:	Wash hands, forearms, and face thoroughly with plenty of soap and water after handling chemical products, before eating, smoking, and using the restroom and at the end of the working period. Appropriate engineering, administrative, and other best practice decontamination control measures must be used to isolate contaminates on clothing and to prevent unintended migration of contaminants. Handle clothing and other potentially contaminated material appropriately and in compliance with local, state, and federal regulations in the process of removing, washing/cleaning, and reuse of these potentially contaminated materials. Ensure compliant use and location of eyewash station and safety showers.				
PERSONAL PROTECTIVE	EQUIPMENT (PPE):	BELLEVILLE OF THE PROPERTY OF			
EYE PROTECTION:	indicates this is necessary to av	an approved standard should be used roid exposure to liquid splashes, mists, on should be worn, unless the assessm splash goggles and/or face shield.	or dusts. If contact is		
SKIN PROTECTION:	Personal protective equipment performed, the risks involved, a handling this product.	for the body should be selected based nd should be approved by an industria	on the task being I hygiene specialist before		
HANDS PROTECTION:	Chemical resistant gloves complying with applicable health and safety standards shall be worn when handling this product. Protective gloves are those made from butyl rubber, nitrile rubber, or polyvinyl alcohol. Appropriate hazard assessments in conjunction with an evaluation of the protection factors of chemical resistant gloves shall be performed to ensure the protective properties remain intact. It is noted that the time to breakdown of protection factors for different glove manufacturers varies. In the case of mixtures, the protection factors of chemical resistant gloves may be impacted and deteriorate at unpredictable rates without understanding the impact of the substance and the specific protection factors of the chemical resistant gloves.				
RESPIRATORY PROTECTION:	appropriate use a full-face partical cartridges as a backup to engiruse a full-face supplied respirat	Ensure adequate ventilation. Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).			
ENVIRONMENTAL EXPOSURE CONTROLS:	Dispose of raw and spent materials and wastes in compliance with all local, state, and federal regulations to prevent potential environmental contamination. Industrial air monitoring may be required to determine any potential environmental hazards to the atmosphere. This monitoring may result in the use of engineering and administrative controls such as filtering and scrubbing systems to mitigate or eliminate potential contaminants.				
SECTION 9: PHYSICAL 8	CHEMICAL PROPERTIES				
PHYSICAL STATE:	Liquid	FLASH POINT:	Not available		
COLOR:	Light yellow	AUTO-IGNITION TEMPERATURE:	Not available		
ODOR:	Amine odor	DECOMPOSITION TEMPERATURE:	Not available		
ODOR THRESHOLD:	Not available	EXPLOSIVE LIMITS:	Not explosive		
pH:	Not applicable	FLAMMABILITY:	Not available		
WATER SOLUBILITY:	Not available	BOILING POINT:	Not available		
PARTITION COEFFICIENT:	Not available	BOILING RANGE:	Not available		
SPECIFIC GRAVITY:	1.05±0.01 g/cc @ 77°F (25°C)	MELTING/FREEZING POINT:	Not available		
VISCOSITY:	700±100 cps @ 77°F (25°C)	VAPOR PRESSURE:	Not available		
EVAPORATION RATE:	Not available	VAPOR DENSITY:	Not available		
VOC:	Not available	RELATIVE DENSITY:	8.8±0.05 lbs/gal		

SECTION 10: STABILITY	REACTIVITY				
STABILITY:	Stable when hand	lled and stored at temp	eratures 60-90°F (15-32°C		
INCOMPATIBILITY:	Will react with isocyanates, oxidizing materials, strong acids, and strong bases.				
HAZARDOUS REACTION:	No information available.				
HAZARDOUS POLYMERIZATION:	No information av	No information available.			
CONDITIONS TO AVOID:	Avoid moisture co	entamination in containe	ers, avoid high temperatu	ires.	
HAZARDOUS DECOMPOSITION:	No information av	ailable.		a a	
SECTION 11: TOXICOLOG	Y INFORMATION				
ACUTE HEALTH EFFEC	TS:				
EYE CONTACT:	Causes eye irritati	ion.			
SKIN CONTACT:	Causes skin irritat				
INHALATION:		inhaled and may cause	respiratory irritation		
INGESTION:	Harmful if swallow		respiratory initiation.		
ACUTE TOXICITY:	1				
COMPONENT NAME	CAS NUMBER	LD <sub>50</sub> Oral (mg/kg)	LD <sub>50</sub> Dermal (mg/kg)	LC <sub>50</sub> Inhalation (mg/m³/4hrs)	
Polyether polyol	25791-96-2	>2,000 (rat)	>2,000 (rabbit)	Not available	
Polyether polyol	9049-71-2	Not available	Not available	Not available	
Triethanolamine	102-71-6	>4,000 (rat)	>2,000 (rabbit)	Not available	
Ethanol, 2-(dimethyamino)-	108-01-0	1,182 (rat)	>3,000 (rabbit)	1,641 (rat)	
Dipropylene glycol	25265-71-8	14,800 (rat)	20,500 (rabbit)	3,000-4,000 (rat)	
Triethylenediamine	280-57-9	1,700 (rat)	>2,000 (rat)	20,200 (rat)	
Copolymer of dimethylsiloxane and polyoxyalkyene	68937-45-2	Not available	Not available	Not available	
Dibutylin dilaurylmercaptide	1185-81-5	>2,000 (rat)	1,000-2,000 (rabbit)	Not available	
POTENTIAL CHRONIC EFFEC	TS:				
CHRONIC EFFECTS:	Repeated ingestio	n or swallowing may inj	ure internally.		
TARGET ORGANS:	None known.				
CARCINOGENICITY:	As of this publicati Carcinogens. Plea	on, this material is not li	isted on the National Tox cent information with NTF	ic Program (NTP) Report of	
MUTAGENICITY:	Control of the Contro	ant effects or critical haz			
TERATOGENICITY:		ant effects or critical haz		rgua/*\u00e4	
FERTILITY EFFECTS:	No known significa	ant effects or critical haz	zards.		
DEVELOPMENTAL EFFECTS:	No known significa	ant effects or critical haz	ards.	Secret Macros 17	
MEDICAL CONDITIONS AGGRAVATED BY OVER-EXPOSURE:	Existing respiratory/pulmonary and skin conditions may be aggravated by overexposure.			ated by overexposure.	

#### SECTION 12: ECOLOGICAL INFORMATION

ENVIRONMENTAL EFFECTS:

Based on a review of the individual components this product may be immediately harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment and is not readily biodegradable.

#### SECTION 13: DISPOSAL CONSIDERATION

#### WASTE DISPOSAL:

By-product wastes or process waste generation should be eliminated and/or minimized when possible. Do not dispose of any contaminants into sanitary sewer systems, storm drains, Publicly Owned Treatment Works (POTW), or any other municipal waste water treatment facility without written approval and agreements for processing wastes with such enterprises. Dispose of raw or unused materials, wastes, and/or by-products in accordance with all applicable local, state, and federal laws. Employ the expertise and knowledge of qualified personnel or contractors in disposal of any and all variants of this product. Ensure material containers are cleaned to the applicable standards before recycling, disposing, or reusing containers. Take special precautions to avoid any cross contamination and potential unknown effects from mixing with other substances. Refer to SECTION 8: EXPOSURE CONTROL/ PERSONAL PROTECTION of this document for personal protection requirements. Disposal to the environment or in violation of environmental protection laws and statutes must be prevented.

#### **SECTION 14: TRANSPORT INFORMATION**

#### PROPER SHIPPING NAME:

DOT:	Not regulated.
TDG:	Not regulated.
IMDG:	Not regulated.
IATA:	Not regulated.

This product could potentially contaminate aquatic and terrestrial environments if not handled in accordance with all precautions, regulations, and laws. Users, transporters, and all other applicable entities must review, follow, and apply any and all necessary precautions and procedures to eliminate and/or minimize potential hazards or risks to aquatic or terrestrial environments.

#### SECTION 15: REGULATORY INFORMATION

#### **U.S. Federal Regulations**

This material is not hazardous to health under OSHA Hazard Communication Standard (29 CFR 1910.1200)

No components listed.

HCS Classification:	Toxic Irritant
TSCA 8b Inventory:	All components are listed on the TSCA inventory or are exempt.
TSCA 5a (2):	No components listed.
TSCA 5e:	No components listed.
TSCA 12b:	No components listed.
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs):	No components listed.
Clean Air Act - Ozone Depleting Substances (ODS):	This product does not contain nor is it manufactured with ozone depleting substances.
SARA 313 Form R - Reporting Requirements:	No components listed.
SARA 311/312 hazard identification:	Immediate (acute) health hazard. Delayed (chronic) health hazard.

#### **CERCLA Hazardous substances:**

#### STATE REGULATIONS:

**CERCLA Hazardous** 

substances:

PENNSYLVANIA/NEW	COMPONENT	CAS NUMBER	CONCENTRATION
JERSEY/MASSACHUSETTS - RTK:	Ethanol, 2-(dimethyamino)-	108-01-0	1-10 %
	Dipropylene glycol	25265-71-8	<1 %
California Prop 65:	This product contains no listed substances known to the State of California to cause cand birth defects, or other reproductive harm, at levels which would require a warning under t statute.		

CANADA		
WHMIS (Canada): WHMIS Class D-2A: Material causing other toxic effects (very toxic). WHMIS Class D-2B: Material causing other toxic effects (toxic).		
CEPA DSL:	All components are listed or exempted.	
This product has been classifi and the SDS contains all the in	ed in accordance with the hazard criteria of the Controlled Products Regulations nformation required by the Controlled Products Regulations.	
INTERNATIONAL LISTS:		
Australia inventory (AICS):	All components are listed.	
China inventory (IECSC):	All components are listed.	
Japan inventory:	All components are listed.	
Korea inventory:	All components are listed.	
New Zealand inventory of Chemicals (NZIoC):	Information not available.	
Phillipines inventory (PICCS):	All components are listed.	

#### **SECTION 16: OTHER INFORMATION**

NF	NFPA & HMIS	
4	Extreme	
3	Serious	
2	Moderate	
1	Slight	
0	No Hazard	



## National Fire Protection Association (NFPA)





## Hazardous Material Information System (HMIS)

HEALTH	1	
FLAMMABILITY	1	
REACTIVITY	1	
SPECIAL INFORMATION		

Note: The customer is responsible for determining the PPE code for this material. At the time of publishing, the NFPA/HMIS and the New GHS scale had opposite scales of severity. Check the most recent publications for current information.

Date of Issue:	8/24/2016
Date of previous issue:	
For Your Protection:	The information and recommendations in this publication is to the best of our knowledge, reliable. The toxicity and risk characteristics of products made by Safe Basements LLC will necessarily differ from the toxicity and risk characteristics that occur when such products are used with other materials during a manufacturing process. The resulting risk characteristics should be determined and made known to ultimate end-users and processors. The user is responsible to comply with all applicable federal, provincial or municipal laws and regulations. Safe Basements LLC MAKES NO WARRANTIES OF ANY KIND, EXPRESSED OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.
Preparation Information:	This SDS supersedes <b>ALL</b> previous SDS versions.